


EYE & EYE WEB SLING CAPACITY CHART

	Rated Capacity (lbs.)				Eye Dimensions			Approximate Sling Weight (lbs.)		
	Part Number	Web Width (inches)	Vertical	Choker	Vertical Basket	Width (inches)	Length (inches)	Min. Standard Length (ft)	Base	Adder/ft.
One Ply	EE191	1	1,600	1,250	3,200	1	9	3	.4	.06
	EE192	2	3,200	2,560	6,400	2	9	4	.9	.12
	EE193	3	4,800	3,840	9,600	1 1/2	9	4	1.4	.18
	EE194	4	6,400	5,120	12,800	1 1/2	12	4	1.9	.24
	EE196	6	9,600	7,680	19,200	2	14	5	3.4	.36
	EE198	8	12,800	10,240	25,600	3	18	6	5.3	.48
	EE1910	10	16,000	12,800	32,000	4	22	8	8.0	.60
	EE1912	12	19,200	15,360	38,400	5	26	8	9.8	.72
Two Ply	EE291	1	3,200	2,560	6,400	1	9	3	.4	.13
	EE292	2	6,400	5,120	12,800	2	9	3	.9	.25
	EE293	3	9,300	7,440	18,600	2	12	4	1.7	.38
	EE294	4	11,500	9,200	23,000	2	12	4	2.3	.50
	EE296	6	16,500	13,200	33,000	2	14	6	4.9	.76
	EE298	8	22,750	18,200	44,500	3	18	6	6.5	1.0
	EE2910	10	28,400	22,720	56,800	4	22	7	9.4	1.3
	EE2912	12	34,100	27,280	68,200	5	26	8	13	1.5
Three Ply	EE391	1	4,100	3,280	8,200	1	12	4	1.0	.20
	EE392	2	8,300	6,640	16,600	2	12	4	2.1	.40
	EE393	3	12,500	10,000	25,000	1 1/2	18	5	3.7	.59
	EE394	4	16,000	12,800	32,000	2	18	5	5.0	.79
	EE396	6	23,000	18,400	46,000	3	20	5	7.6	1.2
	EE398	8	30,700	24,560	61,400	4	24	7	13	1.6
	EE3910	10	36,800	29,440	73,600	5	28	7	16	2.0
	EE3912	12	44,000	35,200	88,000	6	32	7	20	2.4
Four Ply	EE491	1	6,200	4,960	12,400	1	12	4	1.1	.26
	EE492	2	12,400	9,920	24,800	2	12	4	2.2	.53
	EE493	3	17,000	13,600	34,000	1 1/2	18	5	4.1	.79
	EE494	4	22,000	17,600	44,000	2	18	5	5.5	1.1
	EE496	6	33,000	26,400	66,000	3	20	5	8.3	1.6
	EE498	8	44,000	35,200	88,000	4	24	7	15	2.1
	EE4910	10	55,000	44,000	110,000	5	28	7	19	2.6
	EE4912	12	66,000	52,800	132,000	6	32	7	23	3.2

**Before ordering slings that are going to be used in a chemically active environment, contact Saltwater Sling & Supply, to recommend the right sling for the right usage.*

Chemically Active Environments can affect the strength of webbing slings in varying degrees, ranging from little to total degradation.



WARNING

SLING FAILURE CAN CAUSE
DEATH OR INJURY
SLING FAILURE RESULTS FROM
MISUSE, DAMAGE, AND
EXCESSIVE WEAR

ADHERE TO INDUSTRY
STANDARDS & REGULATIONS